

Model	Voltage (V)	Capacity (AH)*	Case Pack**	Dimensions H x W x L mm	Weight Each (kgs)	Terminal
ABS 6-1.2	6	1.2	40.0	97 x 24 x 56	0.3	4.8mm Faston
ABS 6-1.3	6	1.3	40.0	58 x 24 x 97	0.3	4.8mm Faston
ABS 6-4	6	4	20.0	106 x 47 x 70	0.78	4.8mm Faston
ABS 6-7	6	7	12.0	99 x 35 x 151	1.21	4.8mm Faston
ABS 6-10	6	10	12.0	99 x 50 x 151	2.06	4.8mm Faston
ABS 6-12	6	12	12.0	151 x 50 x 99	2.45	4.8mm Faston
ABS 12-0.8	12	0.8	40.0	62 x 23 x 94	0.5	Molex Connector
ABS 12-2	12	2	20.0	66 x 35 x 178	0.93	4.8mm Faston
ABS 12-4	12	4	10.0	106 x 70 x 90	1.59	4.8mm Faston
ABS 12-5	12	5	10.0	107 x 70 x 90	1.5	4.8mm Faston
ABS 12-7	12	7	8.0	99 x 65 x 151	2.36	4.8mm Faston
ABS 12-9	12	9	8.0	115 x 65 x 151	2.9	4.8mm Faston
ABS 12-12	12	12	6.0	99 x 98 x 151	3.89	4.8mm Faston
ABS 12-18	12	18	4.0	167 x 75 x 180	5.6	5mm Bolted
ABS 12-24	12	24	1.0	125 x 165 x 175	7.85	5mm Bolted
ABS 12-26	12	26	1.0	165 x 125 x 175	8.5	5mm Bolted
ABS 12-30	12	30	1.0	172 x 132 x 197	11	6mm Bolted
ABS 12-33	12	33	1.0	196 x 130 x 162	10.5	6mm Bolted
ABS 12-40	12	40	1.0	172 x 165 x 197	12.5	6mm Bolted
ABS 12-45	12	45	1.0	211 x 137 x 228	16	6mm Bolted
ABS 12-50	12	50	1.0	228 x 137 x 210	16	6mm Bolted
ABS 12-55	12	55	1.0	211 x 137 x 228	16.9	6mm Bolted
ABS 12-65	12	65	1.0	179 x 172 x 327	20	6mm Bolted
ABS 12-75	12	75	1.0	220 x 169 x 260	25	6mm Bolted
ABS 12-80	12	80	1.0	215 x 169 x 260	25	6mm Bolted
ABS 12-100	12	100	1.0	220 x 172 x 327	28.2	11mm Bolted

Important Notes:

* Rated capacity defined as C20, 20-hour discharge to 1.75 volts per cell at 25°C.

** Preference is for case pack orders or multiples thereof, but we will break a case pack.