



ADVANCED BATTERY SYSTEMS INC.

abs Brand Batteries



Absorbed Glass Mat (AGM) Batteries

- Sealed, maintenance-free technology
- High current discharge characteristics
- UPS, Emergency Lighting, Security, Fire Alarm Panels

Model	Voltage (V)	Capacity (AH) ¹	Case Pack ²	Dimensions L x W x H mm	Weight Each (kgs)	Terminal
ABS 6-1.3	6	1.3	40	97 x 24 x 51	0.28	4.8mm Faston
ABS 6-5	6	5	20	70 x 47 x 101	0.80	4.8mm Faston
ABS 6-7	6	7	10	151 x 35 x 94	1.15	4.8mm Faston
ABS 6-10	6	10	10	151 x 50 x 94	1.54	4.8mm Faston
ABS 6-12	6	12	10	151 x 50 x 94	1.65	4.8mm Faston
ABS 12-2	12	2.2	10	178 x 35 x 62	0.85	4.8mm Faston
ABS 12-4	12	4.5	10	89 x 69 x 101	1.35	4.8mm Faston
ABS 12-5	12	5	10	89 x 69 x 101	1.52	4.8mm Faston
ABS 12-7	12	7.5	8	151 x 65 x 95	2.05	4.8mm Faston
ABS 12-7 F2	12	7.5	8	151 x 65 x 95	2.05	6.4mm Faston
ABS 12-9	12	9	8	151 x 65 x 95	2.50	4.8mm Faston
ABS 12-10.5	12	10.5	6	151 x 65 x 110	2.65	6.4mm Faston
ABS 12-12	12	12	6	151 x 98 x 95	3.20	4.8mm Faston
ABS 12-18	12	18	2	180 x 75 x 167	5.15	5mm Bolted
ABS 12-26	12	26	1	165 x 124 x 174	8.50	5mm Bolted
ABS 12-36	12	36	1	196 x 130 x 162	10.50	6mm Bolted
ABS 12-40	12	40	1	197 x 165 x 175	12.80	6mm Threaded Insert
ABS 12-55G	12	55	1	228 x 137 x 210	16.80	6mm Threaded Insert
ABS 12-65	12	65	1	327 x 172 x 173	20.00	6mm Threaded Insert
ABS 12-70 ³	12	75	1	260 x 169 x 210	22.00	6mm Threaded Insert
ABS 12-80	12	84	1	260 x 169 x 210	24.00	6mm Threaded Insert
NG 12-100	12	105	1	327 x 172 x 216	29.50	8mm Threaded Insert
ABS 12-120 ³	12	120	1	412 x 173 x 233	35.00	8mm Threaded Insert
NG 12-150	12	160	1	483 x 170 x 241	39.20	8mm Threaded Insert
ABS 12-200FR	12	200	1	524 x 240 x 219	60.00	8mm Threaded Insert

Important Notes

➤ 100 % of batteries are tested prior to shipment from factory

1) Rated capacity defined as C₂₀, 20-hour discharge to 1.75 volts per cell at 25°C

2) Preference is for case pack orders or multiples thereof.

3) Non-stock Items may be ordered with 12 week lead time.

FR = UL94-VO Flame retardant case, available on all sizes, standard on the ABS12-200FR